



SUFFIX	MATERIAL	FINISH
S	STAINLESS STEEL 303	CLEAR PASSIVATE

TOLERANCES			
INCH		METRIC	
.XX	±.016	.X	±.4
.XXX	±.005	.XX	±.13

ADDITIONAL BORE SIZE COMBINATIONS AVAILABLE
MAXIMUM BACKLASH: 5 MINUTES OF ARC

CATALOG NO.	BORE1		BORE2		OD		LE		HD1		HD2	
	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM
C02-2493.118	.1181	3.000	.1181	3.000								
C02-2493.124	.1248	3.170	.1248	3.170								
C02-2493.157	.1575	4.000	.1575	4.000								
C02-2493.187	.1873	4.757	.1873	4.757	.750	19.05	.937	23.80	.44	11.2	.44	11.2
C02-2493.196	.1969	5.000	.1969	5.000								
C02-2493.236	.2362	6.000	.2362	6.000								
C02-2493.249	.2498	6.345	.2498	6.345								
C02-2493.118-157	.1181	3.000	.1575	4.000								
C02-2493.124-187	.1248	3.170	.1873	4.757								
C02-2493.157-196	.1575	4.000	.1969	5.000	.750	19.05	.937	23.80	.44	11.2	.44	11.2
C02-2493.187-249	.1873	4.757	.2498	6.345								
C02-2493.196-236	.1969	5.000	.2362	6.000								
C02-32B7.187	.1873	4.757	.1873	4.757					.44	11.2	.44	11.2
C02-32B7.196	.1969	5.000	.1969	5.000					.44	11.2	.44	11.2
C02-32B7.236	.2362	6.000	.2362	6.000					.44	11.2	.44	11.2
C02-32B7.249	.2498	6.345	.2498	6.345	1.000	25.40	1.171	29.74	.44	11.2	.44	11.2
C02-32B7.312	.3123	7.932	.3123	7.932					.56	14.3	.56	14.3
C02-32B7.315	.3150	8.000	.3150	8.000					.56	14.3	.56	14.3
C02-32B7.374	.3748	9.520	.3748	9.520					.56	14.3	.56	14.3
C02-32B7.187-249	.1873	4.757	.2498	6.345					.44	11.2	.44	11.2
C02-32B7.196-236	.1969	5.000	.2362	6.000					.44	11.2	.44	11.2
C02-32B7.236-315	.2362	6.000	.3150	8.000	1.000	25.40	1.171	29.74	.44	11.2	.56	14.3
C02-32B7.249-312	.2498	6.345	.3123	7.932					.56	14.3	.56	14.3
C02-32B7.312-374	.3123	7.932	.3748	9.520					.56	14.3	.56	14.3