



| | MATERIAL | | FINISH | | TOLERANCES | | | |
|--|---------------------|--|-----------------|--|------------|-------|--------|------|
| | BODY & CLAMP | | BRAKE | | INCH | | METRIC | |
| | STAINLESS STEEL 303 | | CLEAR PASSIVATE | | .XX | ±.016 | .X | ±.4 |
| | BRONZE | | OIL IMPREGNATED | | .XXX | ±.005 | .XX | ±.13 |

| CATALOG NO. | BORE | | OD | | LE | | GW | | TORQUE |
|---------------|-------|-------|-----|------|------|------|------|------|----------|
| | IN | MM | IN | MM | IN | MM | IN | MM | |
| SC2-2450.1179 | .1179 | 2.994 | | | | | | | |
| SC2-2450.1248 | .1248 | 3.170 | | | | | | | |
| SC2-2450.1573 | .1573 | 3.995 | | | | | | | |
| SC2-2450.1873 | .1873 | 4.757 | .75 | 19.1 | .48 | 12.3 | .063 | 1.59 | 50 IN OZ |
| SC2-2450.1966 | .1966 | 4.994 | | | | | | | |
| SC2-2450.2360 | .2360 | 5.994 | | | | | | | |
| SC2-2450.2498 | .2498 | 6.345 | | | | | | | |
| SC2-24A1.1248 | .1248 | 3.170 | | | | | | | |
| SC2-24A1.1873 | .1873 | 4.757 | .75 | 19.1 | 1.02 | 25.8 | .125 | 3.17 | 50 IN OZ |
| SC2-24A1.2498 | .2498 | 6.345 | | | | | | | |
| SC2-29A1.1248 | .1248 | 3.170 | | | | | | | |
| SC2-29A1.1873 | .1873 | 4.757 | .91 | 23.0 | 1.02 | 25.8 | .125 | 3.17 | 50 IN OZ |
| SC2-29A1.2498 | .2498 | 6.345 | | | | | | | |
| SC2-3262.1248 | .1248 | 3.170 | | | | | | | |
| SC2-3262.1873 | .1873 | 4.757 | .98 | 25.0 | .63 | 15.9 | .125 | 3.17 | 50 IN OZ |
| SC2-3262.2498 | .2498 | 6.345 | | | | | | | |